CONTENTS OF SITE INVESTIGATION REPORTS FOR PETROLEUM CONTAMINATED SITES

For Submittals to:
The Department of Natural Resources
&
The Department of Commerce

October 2001

RR Publication #RR-628





PURPOSE: This guidance contains requirements found in NR 716, NR 746/Comm 46 [hereafter referenced as NR 746 for brevity] and Comm 47, which specifically pertain to the contents of site investigation reports for petroleum tank discharge sites. This guidance does not apply to other types of sites.

DISCLAIMER: This document is intended solely as guidance and does not contain any mandatory requirements except where requirements found in statute or administrative rule are referenced. This guidance does not establish or affect legal rights or obligations and is not finally determinative of any of the issues addressed. This guidance does not create any rights enforceable by any party in litigation with the State of Wisconsin or the Department of Natural Resources. Any regulatory decisions made by the Department of Natural Resources in any matter addressed by this guidance will be made by applying the governing statutes and administrative rules to the relevant facts.

Site Investigation Reports: A report for soil or groundwater contamination is required by ch. NR 716. A site investigation report is the basis for all subsequent decisions regarding cleanup of a contaminated site. A complete and well-organized report allows state regulators to make better and faster decisions including, in some cases, case closure. If a case closure request will be made at the end of the site investigation, see NR 746.07(1) and publication RR-614, *Interim Guidance on Natural Attenuation for Petroleum Releases*, before completing the site investigation report. Use the case closure request form (Form 4400-202) required by NR 726.05(2).

PECFA and Petroleum Tank Discharge Sites: The Petroleum Environmental Cleanup Fund Act (PECFA) is Wisconsin's reimbursement program for eligible cleanup costs at petroleum tank discharge sites. Some basic PECFA considerations are included in Attachment A of this document, but please see the Department of Commerce web site listed below for additional information about PECFA.

On-line Information Sources:

• Administrative rules: http://www.legis.state.wi.us/rsb/code/codtoc.html

NR 700 Series (includes NR 746)

Comm 47, PECFA

NR 140, Groundwater Quality

NR 141, Groundwater Monitoring Well Requirements

NR 149, Laboratory Certification

- Dept. of Commerce web site: http://www.commerce.state.wi.us/COM/Com-Petroleum.html
 Information on PECFA, staff contacts, etc.
- Dept. of Natural Resources web site: http://www.dnr.state.wi.us/org/aw/rr/index.htm
 Information on environmental cleanup, staff contacts, etc. (Use the "Publications" button for natural attenuation technical guidance, case summary and close out form, etc.)
 Certified Laboratories: http://www.dnr.state.wi.us/org/es/science/lc/search/

Organization of Site Investigation Reports: Site investigation reports should be organized into the following sections. The "Site Investigation Report Contents" table and attachments that follow this outline provide additional details about the information needed in each of the following sections:

Cover Letter and Title Page

Table of Contents

Executive Summary

Sections of Report:

Section 1: Introduction and Background

1.1 Responsible Party Information

1.2 Consultant Information

1.3 Site Location1.4 Site History

Section 2: Geology and Receptors

2.1 Regional and Local Geology and Hydrogeology

2.2 Receptors

Section 3: Site Investigation Results, Risk Criteria

3.1 Methods of Investigation

3.2 Data Discussion

3.3 Permeability and Hydraulic Conductivities (NR 746)

3.4 Discussion of Results

3.5 Contaminant Migration (NR 746)

3.6 Risk Screening Criteria (NR 746)

3.7 Agency Jurisdiction (NR 746)

Section 4: Conclusions

4.1 Summary of Results and Recommendations

4.2 Site Closure Decisions (NR 746)

Section **5**: References Section **6**: Figures

Regional Location Map

Site and Property Maps

Soil Sample Results Summary Maps

• Geologic Cross Sections

Hvdrogeologic Maps

Section 7: Data Tables, Graphs and Statistical Analyses

Soil Analytical Results Summary

Groundwater Elevation and Free Product Interim Action Results

Groundwater Analytical Results Summary

Graphs and Statistical Analyses

Report Appendices:

A Methods of Investigation

B Analytical Methods and Laboratory Data Reports

C Well and Borehole Documentation

D Waste Disposal Documentation

E Other Documentation

NR 716.01 states:

"Nothing in this chapter shall be construed to require plans or reports that are more detailed or complex than is justified by the known scope of contamination or the complexity of the site or facility."

Site Investigation Report Contents

Note: Items listed here are reporting requirements. Other rule requirements may apply.

Sec	Item	Code Reference	e Contents						
360			_						
	Cover Letter and	NR 716.15(2)(a)		Include identification numbers (e.g., BRRTS #					
	Title Page			and Comm #), purpose of the submittal, and					
				desired agency response					
		recommended	Include site name and address						
		NR 712.09		Professional certification					
	Table of Contents	recommended	 Organization of the report (Sections 1-7 and 						
			appendices)						
	Executive	recommended	Summarize Site History: land use, ownership						
	Summary	recommended	_	property and contaminant source locations, other					
	Summary								
	[Drawida a definitiva	,,	_	potential sources					
	[Provide a definitive			Brief Environmental History: historic releases,					
	statement for each			previous investigations, emergency, interim, or					
	bullet point. For			remedial actions conducted, reason for current					
	example, if no off- site potable wells are			investigation					
	present, indicate as	u		Summarize Site Soil Conditions: type(s),					
	such with a			stratification, depth to bedrock					
	statement]	NR 716.15(2)(c)		Summarize Soil Contamination: source and					
	Statement	(/(/		type(s) of contaminants (petroleum and non-					
				petroleum), where detected - accessible and					
				inaccessible					
		recommended		NR 746.06 risk screening, including evaluation of					
		recommended	_	groundwater and direct contact risks					
		wa a a mama a nada d		0					
		recommended		Summarize Groundwater Conditions: depth to					
				groundwater, flow direction, vertical gradients or					
				perched layers, preferential migration pathways					
		NR 716.15(2)(c)		Summarize Groundwater Contamination: type(s)					
				of contaminants (petroleum and non-petroleum),					
				where detected, and migration					
		recommended		Evaluation of Comm 47.337 environmental					
				factors and NR 746.06 risk screening criteria					
		recommended		Summarize impacts and potential impacts to on-					
				site and off-site wells and other receptors, such					
				as surface waters, and vapor hazards in					
				buildings and utilities					
		NR 716.15(2)(c)		Conclusions, including jurisdiction and					
		141(710.10(2)(0)	_	recommendations (i.e., send to public bidding)					
		rocommondod		` ' '					
		recommended		Summarize the risk factors that determine					
		<u> </u>		site jurisdiction					
	on 1: Introduction a		1						
1.1	Responsible	NR 716.15(2)(d)2		Name, address and telephone number of the					
	Person Information			responsible person(s) and property owner (if					
				different from responsible person)					
		recommended		Other concerned persons: adjacent property					
				owners, mortgage holder, attorney, etc.					
1.2	Consultant	NR 716.15(2)(d)3		Name, address and telephone number of					
'	Information	141(/ 10.10(2)(u)0		consultant(s)					
	าเกษากลเปก			consultant(s)					

1.3	Site Location	NR 716.15(2)(d)4		Street address and municipality		
		u		Geographic location by quarter-quarter section,		
				township, range and county		
		NR 716.15(2)(d)7.		Geographic position for all properties within or		
		&		partially within the contaminated site		
		NR 716.15(2)(k)		boundaries, including name of county where site		
				is located; geographic coordinate collection		
				method & scale or resolution of original source		
				of geographic position for on-screen digitizing		
		NR 716.15(2)(j)1.		A copy of the most recent deed with the legal		
				description for all properties		
		NR 716.15(2)(j)2.		A copy of the certified survey map or relevant		
				portion of the recorded plat map, if referred to in		
		ND = 40 4 = 40 // 10 0		the legal description		
		NR 716.15(2)(j)3.		The parcel identification number for each		
			property if the county uses parcel i.d. numbers			
			Note: NR 726.05(3)4. Requires documents no			
				larger than 81/2" x14" for scanning into GIS		
4.4	Cita I liatam	ND 740 45(0)(a)	_	Registry.		
1.4	Site History	NR 716.15(2)(e)		Historical uses of the property		
		NR 708.15		Contaminant discharges and dates		
				Emergency and interim actions taken Off-site sources of contamination		
Sooti	on 2: Goology and I	NR 716.15(2)(e)1		On-site sources or contamination		
	on 2: Geology and I			Coolegie and hydrogoplegie sharesteristics of		
2.1	Regional & Local	NR 716.(2)(g)1		Geologic and hydrogeologic characteristics of		
	Geology &	"		the site		
	Hydrogeology			Media affected or potentially affected by		
		"		contamination, including bedrock		
				Proximity to other contaminant sources		

2.2	Receptors	NR 716.15(2)(g)1	□ Potential or known impacts to receptors:
		, , , ,	 Buildings, basements, sumps, etc.
			 Existing and former utility corridors (include a
			statement concerning the depth of the utility
			corridor)
			 Water supply wells (for both municipal and
			private wells, a definitive statement from the
			consultant representing his or her
			professional opinion on the presence and
			location of any receptor wells. Include
		u	analyses of on-site water supply wells)
			Impacts to habitats, wetlands, outstanding
		í.	resource waters (NR 102.10 & 102.11) Locations of water supply wells within 1200 feet
			of the edge of contamination.
		recommended	□ For municipal wells within 1200 feet of the edge
			of contamination:
			 Well constructor's forms and/or sample logs
			(included in appendix), labeled to
			correspond with mapped locations
			 Confirmation of well locations by phone
		recommended	contact with the municipal utility
		recommended	□ For private wells within 1200 feet of the edge of
			contamination:
			Well constructor's forms and/or sample logs (included in appendix), labeled to
			(included in appendix), labeled to correspond with mapped locations
			 For areas not on municipal well service, field
			verification of well locations within 1200 feet
			of the edge of contamination
			 For areas on municipal well service,
			confirmation by phone contact with the
			municipal utility or health department to
			identify private wells within 1200 feet of the
			edge of contamination
	on 3: Site Investigat	-	
3.1	Methods of Investigation	NR 716.15(2)(g)2	 Dates and types of field work, sequence of activities
	mvestigation	recommended	□ Site access problems [NR 716.11(4) requires
		recommended	that the Department be notified within 30 days if
			access needed to complete the site investigation
			is denied]
		NR 716.15(2)(g)3	□ Analytical methods
		recommended	 Deviations from standard practices, including the
			workplan, and reasons for incomplete sample
			collection

3.2	Data Discussion	NR 716.15(2)(g)3		Water supply well analyses			
0	Data Diocacción	"		Field measurements and observations			
		u		Sample locations, depths and sampling dates			
	See Attachment	"		Sample parameters, specify filtered samples			
	B for Data Table	"		Other sampling data sources (sumps, extraction			
	Presentations			wells, etc.)			
	Fresentations	í,		Observation of other contaminants			
	(nyovido tobloo in	ű					
	(provide tables in	"		Laboratory name			
	Section 7 of report)			Analytical results			
		recommended		Number of groundwater sampling events [NR			
				726.05(3)(a) requires at least 4 quarterly rounds			
				for closure, unless another schedule is			
				approved]			
3.3	Permeability and	NR 746.05(2)(b)		Determine hydraulic conductivities of materials			
	Hydraulic	NR 716.11(3)(c)		where contaminated groundwater is found, per			
	Conductivities			NR 716 or another approved method			
				Determine whether the groundwater plume is			
		NR 746.05(2)(a)5		contained within low permeability material (less			
				than or equal to 10 ⁻⁵ cm/sec) or extends into			
				permeable material			
3.4	Discussion of	NR 716.15(2)(g)2		Sequence of site investigation activities			
	Results	recommended		Flagged data (i.e., exceeds holding time,			
				elevated detection limits)			
		NR 716.15(2)(g)4		Evaluation of inconsistencies between field			
		3 3 ()(3)		observations and laboratory data			
		"		Recommended re-sampling or quality control			
				measures			
		NR 716.15(2)(g)		Lateral and vertical extent and degree of soil and			
		(=)(9)		groundwater contamination			
		ii.					
		u		Impacts to all affected receptors			
		recommended		Risks to potential receptors (including direct			
		recommended	_	contact pathway)			
		NR 708.15(1)		Free product interim action report, if applicable			
		1417 700.10(1)		and not previously submitted			
3.5	Contaminant	NR 746.05(2)(a)6		Evidence of contaminant migration within a utility			
3.5	Migration	NR 746.03(2)(a)6		corridor or permeable soil layer			
	Iviigi autiti	NR 746.05(2)(a)7		Evidence of contaminant migration or imminent			
		NR 746.03(2)(a)7		migration into drain tile, sumps or other points of			
		NFX / 10.11(3)(d)					
		ND 746 05/4\c		entry into buildings			
		NR 746.05(4)a		Determine whether the groundwater plume			
		& ND 746 05(4)b		margin is expanding at sites where the plume			
		NR 746.05(4)b		includes permeable materials [If there is no			
				evidence of plume margin expansion at sites			
				with contamination only in low permeability			
				materials and the most recent release is >10			
				years old, this determination will be assumed]			

3.6	Risk Screening	NR 746.06(2)(a)		Determine whether these Environmental Factors
	Criteria	&		are present:
		Comm 47.337(3)	•	Documented expansion of plume margin
			•	Verified contaminant concentration in a private
				or public potable well greater than the PAL
			•	Contamination within bedrock or within one
				meter of bedrock
			•	Undissolved petroleum product present with a
				thickness of 0.01 feet or more, verified by more
				than one measurement event
			•	Documented contaminant discharge to a surface
		NR 746.06(2)(b-i)		water or wetland
		141(710:00(2)(51)		Determine whether these risk criteria are
				present: Soil contamination that exceeds the soil
			•	screening levels in Table 1 of NR 746.06
				Soil contamination within 4 feet of the surface
				that exceeds the direct contact concentrations in
				Table 2 of NR 746.06
				If identified by the State as contaminants of
				concern, evaluation of other potential human
				health risks from substances within 4 feet of the
				surface
			•	Contamination from releases <10 years old
			•	Evidence of contaminant migration within a utility
				corridor or permeable soil layer
			•	Evidence of contaminant migration or imminent
				migration into drain tile, sumps or other points of
				entry into buildings
			•	ES is attained or exceeded within 1,000 feet of a
				well operated by a public utility
			•	ES is attained or exceeded within 100 feet of any
				well used for human consumption

3.7	Agency Jurisdiction	NR 746.03(7)	•	Determine whether any of these high risk criteria are present: Verified contamination in a private or public potable well that attains or exceeds the PAL Undissolved petroleum product with a thickness of 0.01 feet or more in more than one sampling event ES is attained or exceeded within 1,000 feet of a well operated by a public utility ES is attained or exceeded within 100 feet of any well used for human consumption ES exceedence in fractured bedrock Provide status of non-petroleum contamination, if present
Secti	ion 4: Conclusions			
4.1	Summary of Results and	NR 716.15(2)(I)		Summary of results discussion
	Recommendations	recommended		Recommendations for PECFA eligible tank systems (i.e., public bid for remedy, or closure)
		recommended		Recommendation for all other tank systems/sites (i.e., further action/next submittal or closure)

4.2	Site Closure		Closure consideration at completion of investigation
7.2	Decisions	NR 746.07(1) NR 746.07(2)	For sites with soil contamination only: Satisfies the risk screening criteria (Section 3.6, above) Meets the requirements of NR 726 There is at least a 5 foot separation between soil contamination and the water table; OR For sites with groundwater contamination contained
			within low permeability materials: Satisfies the risk screening criteria (Section 3.6, above) Meets the requirements of NR 726 There is at least a 5 foot separation between the contamination in low permeability material and any underlying or downgradient permeable material OR
			 One of the following requirements is satisfied: All concentrations in permeable materials are below PALs, or Concentrations in permeable materials are below the ES and any PAL exceedences have been granted an exemption, or One of the following tests has been satisfied: Minimum of 4 sampling rounds free of seasonal variation and statistical confirmation that ES exceedences show declining concentrations, or statistical confirmation that ES exceedences demonstrate declining concentrations; OR
		NR 746.07(3)	For sites with groundwater contamination (PAL <conc.<es) (section="" 3.6,="" 726="" above)="" contained="" criteria="" exemption="" granted;="" is="" materials:="" meets="" nr="" of="" or<="" pal="" permeable="" requirements="" risk="" satisfies="" screening="" td="" the="" within=""></conc.<es)>
		NR 746.07(4)	For sites with groundwater contamination (Conc.>ES) contained within permeable materials: Satisfies the risk screening criteria (Section 3.6, above) Meets the requirements of NR 726 Satisfies a statistical test (i.e., Mann-Kendall or Mann-Whitney U tests);OR
Soction	on 5: Poforonooc /c	NR 746.07(5)	Closure under NR 726
Section	on 5: References (s	elf-explanatory)	

Secti	Section 6: Figures						
	Regional Location Map	NR 716.15(2)(d)5		USGS quadrangle map (7.5 minute quadrangle)			
	Site and Property	NR 716.15(2)(d)6		Property lines, roads and buildings			
	Maps (include	"		Surface waters			
	historical	"		Underground utilities			
	structures & land use)	и		Water supply wells within 1200 ft of contamination			
		"		Adjacent land use			
	See footnote	"		Known and potential hazardous substances			
	below for map	recommended		Note surface cover type(s)			
	requirements	NR 716.15(2)(e)1		Contaminant source locations (e.g., spills, tanks and piping, disposal areas)			
		recommended		Pre-site investigation sample locations (all soil			
				and groundwater sample locations)			
		"		Site Investigation sample locations			
	Soil Sample	NR 716.15(2)(g)3		Map of all sample locations, field measurements			
	Results Summary			and summary of laboratory analytical sample			
	Maps			results (including soil sample depths)			
		recommended		Indicate areas that exceed RCLs			
	Geologic Cross	NR 716.15(2)(g)6		Geologic cross sections for sites with two or			
	Sections			more soil borings			
		NR 716.15(2)(h)2		Reduced inset map of site layout on the cross			
				sections, showing locations of transects			
		í,		Dates of field work			
		ű		Stratigraphy			
		"		Screened intervals of wells			
		recommended		High and low water table elevation surfaces			
		"		Field screening results			
		ű		Representative laboratory analytical results			
				(analytes of concern) and depiction of			
				contaminant plume			

	Hydrogeologic	NR 716.15(2)(g)5		Water table map for sites with 3 or more wells			
	Maps	&		Water table elevations measured on the			
		NR		same day			
	See footnote	716.15(2)(h)1.e		Dates of measurements			
	below for map	()()		Direction of flow for a representative amount			
	requirements			of sample events (provide a sufficient			
	7			number of flow maps that reflect the			
				variability present)			
		u		Potentiometric surface maps, when included:			
			_	Water table elevations measured on the			
				same day			
				Date of measurements			
				Direction of flow for each sampling date			
				(provide a sufficient number of flow maps			
				that reflect the variability present)			
				Measurements from similar screen lengths in			
				the same geologic zone and depth			
				Vertical gradients			
				Confining layers			
		NR 716.15(2)(g)7		Isoconcentration maps where data are sufficient:			
				Substance and concentrations			
		recommended		Impacted hydrogeologic unit(s)			
		"		Dates and units of measure			
Footi	notes for Figures: M	lap and Visual Aid F	Seai	uirements			
	irements for quality	recommended	□ Site name and location				
	maps and visual	"		Identification of all sample points			
aids	•	"		11"x17" maximum page size			
		NR 716.15(2)(h)		Appropriate scale to show required details			
		" · · · · · · ·		Figure #, title, north arrow			
		"		Legend of symbols			
		u		Horizontal and vertical scales			
		u		Date and source, if not original			
		"		National geodetic survey elevations			
				Use a distinguishing symbol (i.e., dashed line)			
04	an 7. Data Tables (for inferred conditions			
	on 7: Data Tables, C	-					
	Data tables (See Attachment	NR 716.15(2)(g)3		Tables of cumulative sample results and field measures - soil, groundwater, product			
	B)	NR 720.19(7)		Calculated site specific RCLs, if applicable			
	Graphs	recommended		Graph of concentration over time for each major			
	(See Attachment	7000111111011404		contaminant in each well along the centerline of			
	B)			the plume (contaminant concentrations should			
	-,			be plotted together with water levels)			
		u		Graph of concentration over distance along the			
				centerline of the plume			

	Statistical	NR 746.07(4)(c)		Statistical Analyses (e.g., Mann-Kendall, Mann-		
	Analyses			Whitney U test, etc.)		
Repo	rt Appendices					
Α	Methods of	NR 716.15(2)(f)	R 716.15(2)(f) Subsurface boring and probe method:			
	Investigation	u		Monitoring well construction, installation and		
				development procedures		
		u		Well and aquifer test methods		
		u		Modeling techniques, if used		
		recommended		Sensitivity analysis of modeling results		
		NR 716.15(2)(f)		Sample collection, handling and analysis		
		recommended		Description of elevation survey and survey		
				benchmark location		
В	Analytical Methods	NR 716.15(2)(g)3		Sample extraction and analysis dates		
	& Laboratory Data	ű		Analytical methods		
	Reports	u		Method detection limits		
		recommended		Laboratory analytical data sheets		
С	Well and Borehole	NR 716.15(2)(i)		Form 4400-89, groundwater monitoring well		
	Documentation			information		
		u		Form 4400-113A, monitoring well construction		
		"		Form 4400-113B, monitoring well development		
		"		Form 4400-122, soil boring logs		
		íí		Form 3300-5B (when relevant),		
				well/drillhole/borehole abandonment		
D	Waste Disposal	recommended		Scale tickets for landfilled soil		
	Documentation	"		Pumping receipts for liquid removals		
		"		Tank and sludge disposal		
		и		Disposal records for containerized solid and		
				liquid wastes		
E	Other	recommended		Other information referenced in the report (e.g.		
	Documentation			calculations, letters, phone conversations,		
				photos)		

Submittals:

- For contamination exclusively associated with petroleum storage tank products that display <u>any</u> of the "high-risk" jurisdictional criteria, send site investigation reports to DNR (include the BRRTS #). The risk criteria are listed in Section 3.7. To facilitate the PECFA public bidding process, also send one copy to the Department of Commerce.
- 2. For contamination exclusively associated with petroleum storage tank products that do <u>not</u> display any of the "high-risk" jurisdictional criteria, send one copy of the report to the Department of Commerce (include Commerce claim number, if assigned).
- 3. For site investigations that indicate soil or groundwater contamination by one or more hazardous substances other than petroleum products discharged from a petroleum storage tank that are commingled with petroleum storage tank contamination, send reports to DNR. To facilitate the PECFA public bidding process, also send one copy to the Department of Commerce.
- 4. For site investigations that indicate soil or groundwater contamination by one or more hazardous substances other than petroleum products discharged from a petroleum storage tank but where that plume is <u>not commingled</u> with a plume from a petroleum storage tank (and where there are no "high-risk" criteria associated with the petroleum storage tank plume), send reports to Commerce and to the DNR. Request transfer of the petroleum contamination case to Commerce.

Note: If the site investigation report is sent to Commerce, a copy of the cover letter that states that the case is a "low or medium risk" Commerce site should be sent to the DNR to facilitate file transfer.

ATTACHMENT A Information Regarding PECFA

The Petroleum Environmental Cleanup Fund Act (PECFA) is Wisconsin's reimbursement program for eligible cleanup costs at petroleum tank discharge sites. The Wisconsin Department of Commerce administers PECFA. Please see the Commerce web site for information on PECFA.

Wisconsin Administrative Code Comm 47

Comm 47, Petroleum Environmental Cleanup Fund, is the rule that covers PECFA program eligibility and reimbursement procedures. Important information on control of costs in Comm 47 includes:

- 1. comparison of at least three proposals for site investigations,
- 2. purchase of commodity services through competitive bids,
- 3. consideration of the costs and benefits of remediation alternatives,
- 4. use of environmental factors to determine the eligible range of remedial responses, and
- 5. use of site bundling and competitive bidding to reduce costs.

\$40,000 Site Investigation Cap: Comm 47 limits site investigation reimbursement to \$40,000 unless another amount has been approved by the Department of Commerce.

Interim Action: Additional activities outside the scope of investigation may be performed concurrently to contain or recover a discharge, usually free product, to minimize threats to the environment prior to remediation. Comm 47.337(2)(d) stipulates that \$5,000 maximum may be reimbursed by PECFA, but only if Commerce is notified prior to beginning the interim action activities. Interim action activities can be detailed in the site investigation report, or under separate cover.

Sites Under \$60,000: When Commerce receives a notification of a cost effective remediation per Comm 47.339(2) [total investigation and remedial action costs (including closure costs, but excluding interest) are under \$60,000], the information required in the site investigation report shall be included in a combined report covering investigation and remediation, which may also include a case closure request. Remedial action at most other PECFA sites will be publicly bid to establish the remediation and cost to closure.

Note: Upon receipt of a site investigation report by either Commerce or DNR, the review process is started, and the remediation will be publicly bid. If a site investigation report submittal is followed by a notification of a cost-effective remediation (i.e., remediation will be conducted without Department review), the investigation report will be considered an unnecessary interim environmental report per Comm 47.339(1)(a).

PECFA-Eligible and Ineligible Releases: A petroleum tank discharge site may contain tank systems that are PECFA-eligible and tanks/releases that are not eligible for reimbursement. Both types of releases may be investigated and remediated concurrently. However, per Comm 47.30(4)(b), a methodology for separation of eligible and ineligible costs must be submitted to the Department of Commerce for approval prior to claim submittal.

ATTACHMENT B General Format for Data Tables

Per NR 716.15(2)(h):

- Table #, title, explanation of footnotes
- Units of measure same as relevant environmental standards
- Date(s) of measurements
- Comparison to relevant environmental standards

Recommended:

- Cumulative table of all sample results
- Data tables presented in format below

Example Presentation for Soil Analytical Results Summary

Add additional analyte columns as needed. Units are µg/kg unless otherwise indicated.

Table # , Title

Boring & Sample	Sample Date	Depth* (ft bgs)	PID (ppm eq)	GRO (mg/kg)	Benzene	Ethylbenzene	Toluene	Xylenes (total)
B1-S1	10/25/97	3.5-5.5	985	1400	<0.002	46,000	28,000	226,000
B1-S5	10/25/97	11-13	15	45	190	91	210	450
MW1-S3	12/15/98	6-8	5	<0.36	<20	<12	<11	<39
MW1-S5	12/15/98	11-13	4	<0.36	<20	<12	<11	<39
NR 720.09	NR 720.09 RCLs			100	5.5	2,900	1,500	4,100
NR 746.06 Table 1 (free product indicator)				8,500	4,600	38,000	42,000	
NR 746.06	Table 2 (dire	ect contact s	tandard)		1,100			

ft bgs = feet below ground surface Note:

ppm eq = part per million equivalent

GRO = gasoline range organics

*Data with asterisk indicates sample was taken at or below the historic measured high water table,

based on monitoring well data.

Instructions for Soil Tables:

- Include contaminants without standards (i.e. all detected analytes). Extend table laterally if needed to include all analytes. Use maximum 81/2" x 14" paper size for tables that will be included in case closure requests.
- Include pre-site investigation soil sample results (i.e., site assessment results)
- For individual compounds, use uniform units of measure between reported analyte concentrations and regulatory RCLs
- Provide adjacent property results, if applicable
- Specify field screening methods (i.e., PID, FID)
- Specify method detection limit as <value (not "ND")
- □ Print concentrations below the RCL in black ink
- Print concentrations above the NR 720 RCLs in **bold** type (do not shade or cross hatch cells)
- If site specific RCLs (SSRCLs) are calculated, indicate values by inserting an additional row under NR 720.09 RCLs and indicate soil sample results that exceed the SSRCLs with italic font. See NR 720.19 for procedures and documentation requirements. Include documentation in Appendix E
- Add footnotes beneath table for relevant comments (e.g., operational problems with PID during sampling of B1 boring, pertinent laboratory notes, etc.)

Example Presentation for Groundwater Analytical Results Summary

Add additional analyte columns as needed. Units are µg/kg unless otherwise indicated.

Table # . Title:

MW-2	Тор	of Well Screen (msl):	Length of Well Screen:				
Sample Date	Benzene	Ethylbenzene	Toluene	Xylenes (total)	TMBs (total)	MtBE	Water Level* (ft msl)	
4/3/95	970	180	1,400	750	297	<1.6	866.47	
8/18/95	4,600	530	3,000	1,900	<2.7	<0.80	865.47	
3/4/97	870	220	1,300	820	213	49	865.51	
7/16/97	4,400	570	5,400	2,500	600	<1.6	865.75	
6/12/98	1,700	280	2,300	1,200	316	<1.6	866.25	
12/10/98	4,200	800	5,400	3,600	620	<1.6	865.58	
7/9/99	3,400	560	5,000	2,220	520	<1.6	865.87	
10/8/99	3,600	720	5,000	3,300	640	9.1	865.48	
MW-3	Тор	of Well Screen (msl):	Length of Well Screen:				
4/3/95	860	300	230	1,170	376	<0.21	866.30	
8/18/95	1,800	750	1,200	3,000	650	<0.21	865.39	
3/4/97	0.44	<0.12	<0.11	<1.8	<0.82	<0.21	865.46	
7/16/97	41	6.3	0.69	22	10	<0.21	865.61	
6/12/98	12	4.3	1.8	24	9.1	<0.21	866.13	
12/10/98	600	190	5	293	245	<0.21	865.50	
7/9/99	70	44	10	110	54	<0.21	865.75	
10/8/99	400	85	4.4	62	51	<0.21	865.38	
NR 140 ES	5.0	700	1,000	10,000	480	60		
NR 140 PAL	0.5	140	200	1,000	96	12		

^{*} Asterisk indicates water table well screen submerged below water table


Instructions for Groundwater Tables:

- □ Include contaminants without standards (i.e. all detected analytes). Extend table laterally if needed to include all analytes. Use maximum 81/2" x 14" paper size for tables that will be included in case closure requests.
- □ Natural attenuation parameters can be added, or if space necessitates, a separate table with the same format could be used for these results.
- Should be cumulative tables organized on a per well basis, as shown above
- □ For individual compounds, use uniform units of measure for comparison of reported analyte concentrations to regulatory standards
- □ Water level elevations are to be included for all sample rounds
- □ Present data on Excel[®] spreadsheets; use 10 point font or larger; Agency may request information on disk
- □ Specify method detection limit as <value (not "ND")
- □ Highlight values above the ES in **bold** font (do <u>not</u> shade or cross hatch cells)
- □ Highlight values above the PAL in italics (do not shade or cross hatch cells)
- □ Add footnotes for relevant comments beneath and separate from cells in table (e.g., on ___ (date) well #2 could not be sampled due to ____, pertinent laboratory notes, etc.)
- Specify in footnotes whether samples have been filtered

Recommended Graphic/Statistical Data Presentation

The graph represented below is only one of several that are recommended; other plots include concentration versus distance, and statistical spreadsheet analyses [see comments in Section 7: Data Tables, Graphs and Statistical Analyses, above, and the October 1999 WDNR Publication RR-614 – *Interim Guidance on Natural Attenuation for Petroleum Releases*]

Example Groundwater Elevation and Contaminant Concentration



Note: If shading or colors are used in graphs, there should be sufficient contrast so that details are not lost or obscured when the graph is photocopied.

Example Presentation for Groundwater Elevations with Free Product Interim Action Results

Table # ___, Title__

MW-1							
Surface Elevation		875.23					
Top of Casing Elevation		874.76	Free Product Abatement				
Top of Screen Elevation		870.23					
Bottom of Screen Elevation		860.23					
Measurement Date	DTW (Casing)	Groundwater Elevation	Product Thickness	Product Removed (gallons)	Cumulative Removal (gallons)		
4/3/95	10.15	864.61	1.15	1.5	1.5		
5/15/95	9.65	865.11	1.01	0.75	2.25		
6/25/95	9.35	865.41	0.99	0.5	2.75		
8/18/95	10.33	864.43	0.56	0.25	3		
9/20/95	8.42	866.34	0.12	0	3		
10/4/95	9.75	865.01	0	0	3		
11/9/95	10.02	864.74	1.35	0.75	3.75		
12/16/95	9.75	865.01	0.65	0.25	4		

Note:

- 1) Measurements are in feet; elevations should be relative to mean sea level
- 2) DTW = depth to water (from top of casing)

Instructions:

- □ Wells that have had interim action free product abatement should be plotted individually
- □ Footnote should indicate method of product thickness measurement

Example Presentation for Groundwater Elevations

Table # ___, Title_

MW-2			MW-3			
Surface Elevation		876.56	Surface Elevation			
Top of Casing Elevation		875.99	Top of Casing Elevation			
Top of Screen Elevation		870.85	Top of Screen Elevation			
Bottom of Screen Elevation		860.85	Bottom of Screen Elevation			
Measurement Date	DTW (Casing)	Groundwater Elevation	Measurement Date	DTW (Casing)	Groundwater Elevation	
4/3/95	9.69	866.3		· ·		
8/18/95	10.60	865.39				
3/4/97	10.53	865.46				
7/16/97	10.38	865.61				
6/12/98	9.86	866.13				
12/10/98	10.49	865.5				
7/9/99	10.24	865.75				

Note:

- 1) Measurements are in feet; elevations should be relative to mean sea level
- 2) DTW = depth to water (from top of casing)

